

# MOUNTED OFFSET DISC HARROW



## FEATURES

- Mounted offset disc harrow used in open working field for ploughing, preparation of soil for sowing.
- It can be used in light and medium soil.
- Equipped with high quality boron steel disc with 48-52 HRC hardness.
- Easily transportable as it get easily attached and detached with tractors.
- Available with plain as well as in notched discs.
- Tillage depth of the harrow is 125-180 mm.
- High quality bearings ensure smooth operation with minimum load on tractor.
- High quality seals ensure the prevent of mud and water entry into bearings for long life.

Description	AC-12	AC-14	AC -16	AC-18	AC-20	AC-22	AC-24
Gang Bolt / Axle (mm)	75x10 Angle Frame, 100x50 Channel						
No. of Discs	12	14	16	18	20	22	24
Type pf Discs	Notched disc in front gang & plain disc in rear gang						
Disc diameter (mm)	560 and 580 with 4-6mm thickness						
Width of cut (mm) Apprx	1420	1635	1852	2070	2285	2502	2718
Disc spacing (mm)	230 mm						
Bearing hubs	4		6		8		
Weight (Kgs) Apprx	390	430	500	575	615	675	730
Tractor (HP)	30-40	40-50	50-60	60-70	70-80	80-90	90-100